

## DETERMINATION OF THE MOISTURE CONTENT OF A SOIL - AS 1289.2.1



### AMC 6 DRYING OVEN 450lt - AS 1289.2.1.1

#### WHEN RAPID AIR DRYING IS REQUIRED

Designed to meet the requirements of AS1289 and AS1141 for evaporation for the sodium sulphate test.

Double insulated door for operator safety. All stainless steel interior.

Temperature range Ambient to 150C, VARIATION 2.5c at 105c,

Operates from 240v single phase 15 amp, 3300W

Internal Dimensions 72cmW X 50cmD X 127cmH /450 Litre

External Dimensions 100W X 70D X 170Hcm

Supplied with 6 shelves. Provisions for up to 13 shelves

Fitted with castors for easy location and cleaning. Vermin proof air intake.



### AMC 4 DRYING OVEN 295LT - AS 1289.2.1.1

#### WHEN RAPID AIR DRYING IS REQUIRED

Designed to meet the requirements of AS1289 and AS1141 for evaporation for the sodium sulphate test.

Double insulated door for operator safety. All stainless steel interior.

Temperature range Ambient to 150C, VARIATION 2.5c at 105c,

Operates from 240v single phase 15 amp, 3300W

Internal Dimensions 90 X 65 X 50cm /295Litre

External Dimensions 135 X 90 X 70cm

Supplied with 4 shelves.

Fitted with vermin proof air intake.



### R 2 HOTPLATE - AS 1289.2.1.6

The R 2 Hotplate has a maximum temperature of 350 degrees, 1400W. Dimensions are 406cm long x 203cm wide.



### R 3 HOTPLATE - AS 1289.2.1.6

The R 3 Hotplate has a maximum temperature of 350 degrees, 2400W. Dimensions are 600cm long x 300cm wide x 235cm high.